

GARNET XS4

CNC Controlled Profile Machining Center (4 Axis)



Thanks its spindle which can operate at any angle between -90 / +90 degrees, the 4 axis CNC machining center, GARNET XS4 can process different sizes of aluminum and PVC profiles and offer a wide spectrum of solutions to the user. The Machine is developed to carry out all-in-one milling, drain channel opening, punching, marking and end milling operations on aluminum and PVC profiles, and to perform special non-standard operations on different profiles. The high processing capacity (300 mm x 250 mm) provides satisfactory user experience with the machines' performance in all operations.



By focusing on providing convenient solutions for customers, and combining power and precision, GARNET XS4 lets the processing capacity be only limited by the users imagination, thanks to the 5 kW spindle motor with automatic tool replacement feature.



Thanks to its built-in automatic magazine with capacity for 8 tools, GARNET XS4 saves time when switching to different operations.



With full automatic clamp positioning, GARNET XS4 automates many tasks assuming the work load of the user.



Maintenance of transmission elements is accomplished by the automatic lubrication system which is offered as an optional feature increasing the service life for accuracy in processes. Capacity may be varied for processing of non-standard profiles with on demand optimization of size and number of clamps.



www.oz-machine.com

GARNET XS4

CNC Controlled Profile Machining Center (4 Axis)



MACHINING LENGTHS

X Axis (Longitudinal)	3000 mm
Y Axis (Lateral)	300 mm
Z Axis (Vertical)	250 mm
A Axis (Head rotation movement)	-90° / +90°

POSITIONING SPEED

X Axis (Longitudinal)	127 m/min
Y Axis (Lateral)	40 m/min
Z Axis (Vertical)	10 m/min

SPINDLE

Maximum power	5 kW
Maximum rotation speed	18000 rpm
Tool holder	HSK F50
Cooling type	Liquid

TOOL STORAGE

Tool storage system with stationary ATC	●
Maximum tool storage system number with stationary ATC	8
Tool storage system with umbrella ATC	○
Maximum tool storage system number with umbrella ATC	10
Maximum saw blade diameter in to the storage system	150 mm

PROCESSABLE UNITS

With direct tool (upper surface, lateral surfaces, heads)	5
With saw blade (upper surface, heads)	3

PROFILE POSITIONING

Right and left pneumatic profile reference alignment	●
--	---

CONTROL UNIT

Industrial PC - Touchscreen	15"
Mouse & Keyboard	●
Remote access	●
Data transfer via remote network connection, Ethernet and USB	●
Barcode reader	○
Smart CAM post processing	●

OPERATIONAL AREA

Clamps, standard quantity	4
Clamps, maximum quantity	6
Automatic clamp positioning on X-axis	●
Automatic lubrication in processing area	●
Full guard cabin	●
Side tunnels	○

● Included

○ Optional



www.oz-machine.com